

CURRENT ADT (TO BE USED WHEN NORMAL TRAFFIC COUNTS ARE UNAVAILABLE)					
	ADT EACH HECTARE	MINIMUM ADT EACH PARCEL			
RESIDENCE		10	10		
IRRIGATION FARM LAND					
ROW CROPS	0.020	1.0	8.0		
IMPROROVED PASTURE	0.004	1.0	2.0		
GRANS AND HAY	0.008	2.0	6.0		
TRUCK FARM	0.081	4.0	10.0		
DRY FARM LAND	0.001	2.0	3.0		
GRAZING LAND					
SEMI-IRRIGATION GRAZING	0.002	0.5	2.0		
SEMI-IRRIGATION GRAZING	0.002	1.0	1.0		

LAND USE	CURRENT ADT	TYPICAL SECTION			
RELOCATED CITY STREETS					
DEVELOPED AREAS	UNDER 50	F			
UNDEVELOPED AREAS	UNDER 50	E			
RELOCATED COUNTY ROADS					
	10 - 50	E			
	UNDER 10	D			
PROPERTY ACCESS ROADS					
RESIDENTIAL COMMERCIAL OR INDUSTRIAL AREA					
DEVELOPED AREAS	UNDER 50	F			
UNDEVELOPED AREAS	10 - 50	E			
UNDEVELOPED AREAS	UNDER 10	D			
FARM , PASTURE AND RANGE LAND					
	20 - 50	Ε			
	10 - 20	D			
	5 - 20	С			
	2 - 5	В			
	UNDER 2	Α			



TYPICAL SECTION

THE MINIMUM R/W CLEARANCE OUTSIDE TOE OF SLOPE SHALL BE 6 m OUT SIDE THE TOP OF CUT SLOPES SHALL BE 9 m FOR THOUGH HIGHWAYS AND RAMPS AND 3.0 m FOR FRONTAGE ROADS.



INTERSECTION OF FRONTAGE ROAD AND CROSSROAD

TYDICAL SECTION STANDADOS

TIFICHE SECTION STHINDHRDS						
TYPICAL SECTION	FINISHED SURFACE WIDTH (m)	MINIMUM SUBGRADE WIDTH (m)	APPROXIAE SURFACE THICKNESS(mm)	SURFACE TYPE		
Α	4.3	5.5	150	GRANULAR MATERIAL		
В	4.3	5.5	150	UNTREATED BASE		
С	5.5	6.7	150	UNTREATED BASE		
D	6.7	7.9	150	UNTREATED BASE		
E	7.9	9.1	150	UNTREATED BASE DEEP PENETRATING ASPHALT		
F	7.9		75 225	ASPHALT SURFACING UNTREATED BASE		

FUN TO 3 m (INCLUDING BEDROCK)

PROVIDE BACKSLOPE ROUNDING FOR ALL CUTS STEEPER THAN 1:4 AS PER SLOPE ROUNDING DETAIL. OR AS OTHERWISE DIRECTED BY THE ENGINEER. REFER TO STD. DWG. 815-1

NOTES

- I. PAVEMENT THICKNESS ACCORDING TO USE AND MATERIALS
- 2. FINISHED SURFACE WIDTH MINIMUM ACCORDING TO A.B.C.D E AND F TYPICAL SECTIONS
- 3. A FIXED WIDTH TO THE NEAREST 8.2 m TO PROVIDE 1:4 SLOPE OR FLATTER IN A NORMAL SECTION WITH A 2% OR 3% SLOPE REMANING CONSTANT EVEN THOUGH CONDITIONS OF SUPER FLEVATIONS.
- 4. SUBGRADE WIDTH AS REQUIRED TO ACCOMMODATE 1:4 SLOPE FOR NOTE NO. 3 AND SURFACING WIDTH NOTE NO. 2 MINIMUM WIDTH IN ANY CASE ACCORDING TO A,B,C,D,E AND F TYPICAL
- 5. FRONTAGE ROAD CONNECTION SHALL BE DESIGNED WITH A MINIMUM TURNING RADIOUS OF 18 m AT INTERSECTIONS EXCEPT THAT A TURNING RADIOUS OF 15 m MAY BE USED WHERE FRONTAGE ROAD VOLUMES ARE UNDER 59 ADT. AND NO REGULAR LARGE VEHICLE MOVEMENTS ARE EXPECTED.
- 6. THE MINIMUM R/W CLEARANCE SHALL BE 6 m OUTSIDE THE TOE OF FILL SLOPE FOR THROUGH HIGHWAYS AND RAMPS & 3 m FOR FRONTAGE ROADS.
- 7. DESIGN STANDARDS AS SPECIFIED IN STANDARDS DRAWING 815-3 SHALL APPLY FOR ALL FRONTAGE ROADS OVER 50 ADT.
- 8. TYPICAL SECTIONS A THROUGH F BASED ON C.B.R. VALUE OF 10% OR GREATER.
- 9. THE ENGINEER SHALL DETERMINE THE SUITABILITY OF GRANULAR MATERIAL AVAILABLE ON PROJECT.
- 10. IN RUGGED TERRAIN STEEPER CUT AND FILL SLOPES WILL BE REQUIRED WHEN EXCESSIVE QUANTITIES WOULD RESULT WITH SPECIFIED SLOPES. SLOPES USED SHOULD BE STABLE AS DETERMINED BY GEOLOGICAL AND SOIL INVESTIGATION, SLOPES ARE ALSO SUBJECT TO VARIATION AS MAY BE RECOMMENDED WHERE EXISTING RIGHT OF WAY IS RESTRICTIVE AND COSTS FOR PROVIDING ADDITIONAL RIGHT OF WAY WOULD BE EXCESSIVE, WHERE A DESIGN EXCEPTION TO THE DITCH WIDTHS SHOWN IS TO BE CONSIDERED FOR ROCK CUTS OVER 3 m, ROCKFALL CATCHMENT ANALYSIS WILL BE REQUIRED (SUCH AS RICHIE- 1963), WITH DITCH WIDTHS CONFORMING ACCORDINGLY.
- 11. TRANSITIONS FROM FLAT TO STEEPER CUT AND FILL SLOPES SHALL BE MADE IN SUFFICIENT DISTANCE SO AS TO PROVIDE A NATURAL PLEASING
- 12. TYPICAL DETAILS FOR SECTION ON CURVE, SECTION ON TANGENT, CUT DITCH FLARING AND BENCHED SLOPE SHALL BE IN ACCORDANCE WITH STANDARD DRAWING 815-1.

	DESIGN SPEED (km/h)			
	15	30	50	60
MAXIMUM GRADE - FLAT TERRAIN	8%	8%	7%	7%
MAXIMUM GRADE - ROLLING TERRAIN	12%	11%	10%	9%
MAXIMUM GRADE - MOUNTAINOUS TERRAIN	18%	16%	14%	12%
STOPING SIGHT DISTANCE (m)	15	30	70	90
MINIMUM PASSING SIGHT DISTANCE (m)	250	250	340	460
MINIMUM RADIUS FOR 6% SUPER (m)	12	55	90	135

FRONTAGE STANDARDS ROADS (L STD. DWG. NO. 815-4

Ð

E AND A DS FOR UNDER

- ~ ~ 9

TRANSPORTATION
TO BRIDGE CONSTRUCTION

Ь

DEPARTA

APR.10,2001 DATE APR.10,20

ALL DIMENSIONS ARE SHOWN IN MILLIMETERS (mm) UNLESS OTHERWISE NOTED.